


Distributed Three Port Isolator Assembly

Model 102647

Patent Number 6,407,646,B1



Product Overview

This Isolator Assembly consists of the EM Design Distributed Three Port Circulator, four adjustable E field couplers and an EM Design Waterload-Model R284-3.0.

The straight input Port 1 is on the left side and the output Port 2 is shown on the right side of the photograph. The power reflected at Port 2 is absorbed by the load on Port 3.

The high power S band circulator is based on EM Design's unique patented concept and is especially attractive for isolating reflection from resonant loads such as accelerators or other similar devices. This isolator assembly is set for the 2.998 GHz frequency but can be readily optimized for other frequencies, including 2.856 GHz. Note that the power input, Port 1, and the terminated Port 3 has two variable insertion E field probes (at each port) for monitoring and/or control signals. These probes can be adjusted from the nominal 60 db coupling. Water cooling is connected in series so that the flow is conveyed through the circulator and the attached load.

Unit Specifications

Peak Power	8 MW	Frequency Band	2.998 (+/- 0.010) GHz	2.8 to 3.2 GHz
Average Power	8 KW			
Flanges	CPR284F	VSWR (Port 1)	1.10 max	1.2 max
Water Flow	3.5 GPM			
Water Temperature	25° to 40° C (selectable)	Isolation (Port 1 to Port 3)	>37 db	>33 db
Gas Pressure	35 PSIG SF ₆			
Length	490 mm	Insertion (Port 1 to Port 2)	<0.2 db	<0.25 db
Probe Connector	Type N Female			

22661 Hwy 62
Shady Cove, OR 97539
541-878-3927
Fax: 541-878-3937
www.em-design.com
hjohnson@em-design.com

UNIQUE SOLUTIONS. EXCEPTIONAL PERFORMANCE.

EM DESIGN.LLC